

# BRINE TANKS ASSEMBLIES

## FEATURES & BENEFITS

- High-impact resistant plastics
- Premium quality High-Flow safety brine valve with interchangeable polytube connection ( $\frac{3}{8}$ " or  $\frac{1}{2}$ " )
- Completely pre-assembled
- Equipped with overflow connection, drain hose and proprietary drain connection with air gap



## BRINE TANK SELECTION GRID

✓	Recommended	Brine tank with brine platform and <b>SINGLE</b> brine valve assembly				Brine tank with brine platform and <b>DOUBLE</b> brine valve assembly			
		125Ltr	275Ltr	500Ltr	750Ltr	125Ltr	275Ltr	500Ltr	750Ltr
	OK								
2x	2 pcs required								
	NOT OK								
PF-SOF1-SIM	25Ltr	✓							
	50Ltr	✓							
	75Ltr		✓						
	100Ltr		✓						
	150Ltr		✓						
PF-SOF1-ALT PF-SOF1-PRL	25Ltr	2x				✓			
	50Ltr	2x					✓		
	75Ltr		2x				✓		
	100Ltr		2x					✓	
	150Ltr		2x					✓	
PF-SOF1,5-SIM	75Ltr		✓						
	100Ltr		✓						
	150Ltr		✓						
	200Ltr			✓					
	250Ltr			✓					
	350Ltr			✓					
	500Ltr				✓				
PF-SOF1,5-ALT PF-SOF1,5-PRL	75Ltr		2x				✓		
	100Ltr		2x					✓	
	150Ltr		2x					✓	
	200Ltr			2x				✓	
	250Ltr			2x					✓
	350Ltr			2x					✓
	500Ltr				2x				✓

## TECHNICAL SPECIFICATIONS

Model	PF-BTA			
Volume (Ltr)	125	275	500	750
Hydraulic connection brine valve	interchangeable: $\frac{3}{8}$ " Quick-Fit & $\frac{1}{2}$ " compression fitting			
Hydraulic connection overflow	13 mm hose barb			

## DIMENSIONS & WEIGHTS

Model	PF-BTA			
Volume (Ltr)	125	275	500	750
Diameter (mm) (D)	540	685	875	1030
Height (mm) (H)	850	975	1110	1110
Max. salt storage capacity (kg)	100	200	475	675

